

## Acme Plasticizer

### DESCRIPTION

Acme Plasticizer is designed to make better, more uniform quality concrete block, pipe, etc.

### BENEFITS

- Improves green strength
- Reduces machine wear
- Gives better surface texture
- Reduces absorption
- Eliminates the fine cracks
- Reduces culls and breakage in handling

### HOW TO USE

Acme Plasticizer should be diluted with ten parts of water. This diluted liquid plasticizer may then be dispensed to the mixer through automatic dispensing equipment at the rate of 3 to 4 ounces for each bag of cement in the batch. If there is a preference not to dilute with water, then a one-quarter to one-half ounce of Acme Plasticizer to each bag of cement may be dispersed directly to the batch.

### PHYSICAL FORM

Straw to amber liquid

- uniform consistency
- rust inhibited
- freeze thaw stable

### SHIPPING CONTAINER

55 gallon drum, 330 gallon totes

### COMPANION PRODUCTS

Water Repellents, Rack Coating, Form Release Agents, Accelerators

The information contained herein is believed to be true and correct under US law. All statements, recommendations or suggestions are made without guarantee, express or implied, and are subject to change without notice. We disclaim all warranties, expressed or implied, including any warranties of merchantability, fitness for a particular purpose and freedom from infringement and disclaim all liability in connection with the use of the products or information contained herein.

©2014, Cargill, incorporated. All rights reserved.

[www.cargill.com](http://www.cargill.com)

